



NSF Product and Service Listings

These NSF Official Listings are current as of Monday, January 04, 2016 at 12:15 a.m. Eastern Time. Please contact NSF International to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=46240&>

NSF/ANSI 61

Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of Abbreviations used in these Listings. Click here for the definitions of Water Contact Temperatures denoted in these Listings.

Hilti AG

Feldkircherstrasse 100
FL-9494
Liechtenstein
423 234 2111
[Visit this company's website](#)

Facility : Kaufering, Germany

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Adhesives			
HIT-HY 10 PLUS	[3]	CLD 23	ADH
HIT-HY200[1]	NA	D. HOT	ADH
HIT-HY200-A[1]	NA	D. HOT	ADH
HIT-HY200-R[1]	NA	D. HOT	ADH
HIT-MM Plus	[3]	CLD 23	ADH
HIT-RE 500 V3[2]	NA	D. HOT	ADH
Hilti HIT-CT 1[2]	NA	CLD 23	ADH
Hilti HIT-HY 100[2]	NA	D. HOT	ADH
Hilti HIT-HY 110[2]	NA	CLD 23	ADH
Hilti HIT-HY 150[2]	NA	CLD 23	ADH
Hilti HIT-HY 150 Adhesive Anchoring System[2]	NA	CLD 23	ADH
Hilti HIT-HY 150 Max[2]	NA	D. HOT	ADH
Hilti HIT-HY 150 Max Adhesive Anchoring System[2]	NA	D. HOT	ADH
Hilti HIT-HY 150 Max-SD[2]	NA	D. HOT	ADH
Hilti HIT-HY170	[3]	CLD 23	ADH
Hilti HIT-RE 100	NA	D. HOT	EPOXY
Hilti HIT-RE 500[2]	NA	D. HOT	EPOXY
Hilti HIT-RE 500 Adhesive Anchoring System[2]	NA	D. HOT	EPOXY
Hilti HIT-RE 500 SD[2]	NA	D. HOT	EPOXY
Hilti HIT-RE 500 SD Adhesive Anchoring System[2]	NA	D. HOT	EPOXY
Hilti HIT-HY 150-FR[2]	NA	CLD 23	ADH
Hilti HIT-HY 150-FR Adhesive Anchoring System[2]	NA	CLD 23	ADH

- [1] Certified for use as an anchoring adhesive for installing threaded rods (less than or equal to 32 mm in diameter) in concrete for water treatment applications.
- [2] Product is Certified for use as an anchoring adhesive for installing threaded rods (less than or equal to 1.3 inches in diameter) in concrete for water treatment applications.
- [3] Certified for use as an anchoring adhesive for installing threaded rods (less than or equal to 8 mm in diameter) in concrete or masonry for water treatment applications. Mix ratio of Part A:Part B is 3:1 by volume.

Number of matching Manufacturers is 1
Number of matching Products is 22
Processing time was 0 seconds