

# HIT-RE 500 V3

## Safety information for 2-Component-products

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 26/02/2019

Version: 2.3

### SECTION 1: Kit identification

#### 1.1 Product identifier

Product name

HIT-RE 500 V3



Product code

BU Anchor

#### 1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti Saudi Arabia for Construction Tools LLC  
King Fahd Street  
P.O. Box 15930  
21454 Jeddah - Saudi Arabia  
T +966 2 213 8400 - F +966 2 697 4696  
[sa.customerservice@hilti.com](mailto:sa.customerservice@hilti.com)

### SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

### SECTION 3:

#### Classification of the Product

##### Classification according to the United Nations GHS (Rev. 4, 2011)

Acute Tox. 5 (Oral)	H303
Skin Corr. 1B	H314
Skin Sens. 1	H317
Muta. 2	H341
Repr. 1B	H360
STOT SE 3	H335
Aquatic Chronic 2	H411

#### Label elements

##### Labelling according to the United Nations GHS (Rev. 4, 2011)

Hazard pictograms (GHS UN)



GHS05

GHS07

GHS08

GHS09

Signal word (GHS UN)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS UN)

H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H335 - May cause respiratory irritation.  
H341 - Suspected of causing genetic defects.  
H360 - May damage fertility or the unborn child.

# HIT-RE 500 V3


## Safety information for 2-Component-products

### Precautionary statements (GHS UN)

H411 - Toxic to aquatic life with long lasting effects.  
 P280 - Wear eye protection, protective clothing, protective gloves.  
 P262 - Do not get in eyes, on skin, or on clothing.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P302+P352 - IF ON SKIN: Wash with plenty of water.

### Additional information

2-component-foilpack, contains:  
 Component A: Epoxy resin, Reactive diluent, inorganic filler  
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification according to the United Nations GHS
HIT-RE 500 V3, B		1	pcs	Acute Tox. 5 (Oral), H303 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
HIT-RE 500 V3, A		1	pcs	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

## SECTION 4: General advice

General advice

For professional users only

## SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters  
 Notify authorities if liquid enters sewers or public waters  
 Avoid release to the environment  
 Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.  
 After curing, the product can be disposed of with household waste.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Technical measures

Comply with applicable regulations

Precautions for safe handling

Wear personal protective equipment  
 Avoid contact with skin and eyes  
 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work  
 Avoid contact during pregnancy/while nursing

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation  
 Mechanically recover the product  
 On land, sweep or shovel into suitable containers  
 Store away from other materials.

For containment

Collect spillage.

Incompatible materials

Sources of ignition  
 Direct sunlight

Incompatible products

Strong bases

# HIT-RE 500 V3

## Safety information for 2-Component-products

---

Strong acids

### SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.

### SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

### SECTION 8: Other information

No data available

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 13/05/2020

Version: 1.6

Revision date: 13/05/2020

Supersedes: 25/02/2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500 V3, B
UN-No. (ADR)	3259
Product code	BU Anchor

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
------------------------------	---

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Hilti Saudi Arabia for Construction Tools LLC  
King Fahd Street  
P.O. Box 15930  
21454 Jeddah - Saudi Arabia  
T +966 2 213 8400 - F +966 2 697 4696  
[sa.customerservice@hilti.com](mailto:sa.customerservice@hilti.com)

##### Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH  
Hiltistraße 6  
86916 Kaufering - Deutschland  
T +49 8191 906876  
[anchor.hse@hilti.com](mailto:anchor.hse@hilti.com)

#### 1.4. Emergency telephone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +966 2 213 8400
------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS (Rev. 4, 2011)

Acute Tox. 5 (Oral)	H303
Skin Corr. 1B	H314
Skin Sens. 1	H317
STOT SE 3	H335
Aquatic Acute 3	H402
Aquatic Chronic 3	H412

Full text of H statements : see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS (Rev. 4, 2011)

Hazard pictograms (GHS UN)



GHS05

GHS07

Signal word (GHS UN)

Danger

Hazardous ingredients

2-methyl-1,5-pentanediamine; Phenol, styrenated; m-Xylylenediamine; 3-Aminopropyltriethoxysilan; 2,4,6-tris(dimethylaminomethyl)phenol

Hazard statements (GHS UN)

H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H335 - May cause respiratory irritation.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (GHS UN)

P262 - Do not get in eyes, on skin, or on clothing.  
P280 - Wear eye protection, protective clothing, protective gloves.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention.  
P337+P313 - If eye irritation persists: Get medical advice, medical attention.  
P302+P352 - IF ON SKIN: Wash with plenty of water.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2-methyl-1,5-pentanediamine	(CAS-No.) 15520-10-2	25 - 35	Flammable liquids, Category 4, H227 Acute toxicity (oral), Category 4, H302 Acute toxicity (dermal), Category 4, H312 Acute toxicity (inhalation:dust,mist) Category 4, H332 Skin corrosion/irritation, Category 1A, H314 Serious eye damage/eye irritation, Category 1, H318 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation, H335
Phenol, styrenated	(CAS-No.) 61788-44-1	5 - 10	Skin corrosion/irritation, Category 2, H315 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 2, H401 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
m-Xylylenediamine	(CAS-No.) 1477-55-0	5 - <8	Acute toxicity (oral), Category 4, H302 Acute toxicity (inhalation:dust,mist) Category 4, H332 Skin corrosion/irritation, Category 1B, H314 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, category 1B, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	1 - 2,5	Acute toxicity (oral), Category 4, H302 Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2A, H319
3-Aminopropyltriethoxysilan	(CAS-No.) 919-30-2	1 - 2,5	Acute toxicity (oral), Category 4, H302 Skin corrosion/irritation, Category 1B, H314

Full text of H-statements: see section 16

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.
Potential adverse human health effects and symptoms	No additional information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

##### 6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

##### 6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

### 6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.
------------------------	--

### 8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure good ventilation of the work station.
Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing Long sleeved protective clothing

Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN 374

Eye protection Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red.
Odour	Amine-like.
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.31 g/cm <sup>3</sup>
Solubility	insoluble in water.



# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	50 - 70 Pa·s HN-0333
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Corrosive vapours.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	May be harmful if swallowed.
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

<b>2-methyl-1,5-pentanediamine (15520-10-2)</b>	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 inhalation rat (mg/l)	4.9 mg/l
<b>Phenol, styrenated (61788-44-1)</b>	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	158.31 mg/l/4h
<b>m-Xylylenediamine (1477-55-0)</b>	
LD50 oral rat	1090 mg/kg
LD50 oral	660 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.34 mg/l/4h

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

<b>3-Aminopropyltriethoxysilan (919-30-2)</b>	
LD50 oral rat	1.57 ml/kg
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 11.5
Serious eye damage/irritation	Serious eye damage, category 1, implicit pH: 11.5
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Harmful to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute))	Calculation method
Hazardous to the aquatic environment, long-term (chronic)	Harmful to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	Calculation method

<b>2-methyl-1,5-pentanediamine (15520-10-2)</b>	
LC50 fish 1	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l

<b>Phenol, styrenated (61788-44-1)</b>	
LC50 fish 1	5.6 mg/l
LC50 other aquatic organisms 1	9.7 mg/l
EC50 Daphnia 1	1.44 mg/l
NOEC (acute)	3.2 mg/l
Threshold limit algae 1	0.326 mg/l (72 h; Algae)
Threshold limit algae 2	0.14 mg/l (72 h; Algae)

<b>m-Xylylenediamine (1477-55-0)</b>	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb
EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l

<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LC50 fish 1	> 100 mg/l (96 h; Pisces; Nominal concentration)
EC50 Daphnia 1	10 - 100 mg/l (Invertebrata; Estimated value)
EC50 other aquatic organisms 1	84 mg/l (72 h; Desmodismus subspicatus; growth rate; ECHA)

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

LC50 fish 2	70.9 mg/l (96 h; Pisces)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Threshold limit algae 1	10 - 100, Algae
Threshold limit algae 2	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)

### 12.2. Persistence and degradability

<b>HIT-RE 500 V3, B</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.
<b>Phenol, styrenated (61788-44-1)</b>	
Biochemical oxygen demand (BOD)	0.000231 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.004827 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

<b>HIT-RE 500 V3, B</b>	
Bioaccumulative potential	Not established.
<b>2-methyl-1,5-pentanediamine (15520-10-2)</b>	
Log Pow	0.27 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
<b>Phenol, styrenated (61788-44-1)</b>	
BCF fish 2	3246 mg/l
Log Pow	6.24 - 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Bioaccumulative potential	Bioaccumulative potential.
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Log Pow	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

### 12.4. Mobility in soil

<b>2-methyl-1,5-pentanediamine (15520-10-2)</b>	
Log Pow	See section 12.1 on ecotoxicology
<b>Phenol, styrenated (61788-44-1)</b>	
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test) data on mobility of the substance available.
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available
Other information	Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
<b>14.1. UN number</b>			
3259	3259	3259	3259
<b>14.2. UN proper shipping name</b>			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
<b>Transport document description</b>			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
<b>14.3. Transport hazard class(es)</b>			
8	8	8	8
<b>14.4. Packing group</b>			
II	II	II	II
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	

Tunnel restriction code (ADR) E

#### - Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
Stowage and segregation (IMDG)	Separated from acids.
MFAG-No	154

### - Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

### - Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08
Carriage prohibited (RID)	No

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

## SECTION 16: Other information

SDS Major/Minor	None
Issue date	13/05/2020
Revision date	13/05/2020
Supersedes	25/02/2019

Indication of changes:

Section	Changed item	Change	Comments
2.1	Classification (GHS UN)	Modified	

# HIT-RE 500 V3, B

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE - Acute Toxicity Estimate  
BCF - Bioconcentration factor  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
IATA - International Air Transport Association  
EC50 - Median effective concentration  
IMDG - International Maritime Dangerous Goods  
LC50 - Median lethal concentration  
LD50 - Median lethal dose  
LOAEL - Lowest Observed Adverse Effect Level  
NOAEC - No-Observed Adverse Effect Concentration  
NOAEL - No-Observed Adverse Effect Level  
NOEC - No-Observed Effect Concentration  
PBT - Persistent Bioaccumulative Toxic  
PNEC - Predicted No-Effect Concentration  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
SDS - Safety Data Sheet  
vPvB - Very Persistent and Very Bioaccumulative  
None.

### Other information

#### Full text of H-statements:

H227	Combustible liquid
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS\_UN\_Hilti

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 13/05/2020

Version: 2.3

Revision date: 13/05/2020

Supersedes: 25/02/2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	Mixture
Product name	HIT-RE 500 V3, A
UN-No. (ADR)	1759
Product code	BU Anchor

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
------------------------------	---

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Hilti Saudi Arabia for Construction Tools LLC  
King Fahd Street  
P.O. Box 15930  
21454 Jeddah - Saudi Arabia  
T +966 2 213 8400 - F +966 2 697 4696  
[sa.customerservice@hilti.com](mailto:sa.customerservice@hilti.com)

##### Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH  
Hiltistraße 6  
86916 Kaufering - Deutschland  
T +49 8191 906876  
[anchor.hse@hilti.com](mailto:anchor.hse@hilti.com)

#### 1.4. Emergency telephone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +966 2 213 8400
------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS (Rev. 4, 2011)

Skin Corr. 1C	H314
Skin Sens. 1	H317
Muta. 2	H341
Repr. 1B	H360
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Full text of H statements : see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS (Rev. 4, 2011)

Hazard pictograms (GHS UN)



Signal word (GHS UN)

Danger

Hazardous ingredients

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; butanedioldiglycidyl ether ; 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; trimethylolpropane triglycidylether

Hazard statements (GHS UN)

H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H341 - Suspected of causing genetic defects.  
H360 - May damage fertility or the unborn child.  
H411 - Toxic to aquatic life with long lasting effects.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### Precautionary statements (GHS UN)

P262 - Do not get in eyes, on skin, or on clothing.  
 P280 - Wear eye protection, protective clothing, protective gloves.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention.  
 P337+P313 - If eye irritation persists: Get medical advice, medical attention.  
 P302+P352 - IF ON SKIN: Wash with plenty of water.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	(CAS-No.) 1675-54-3	25 - 40	Flammable liquids Not classified Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 2, H401 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5	10-20	Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
butanedioldiglycidyl ether	(CAS-No.) 2425-79-8	5 - 10	Acute toxicity (oral), Category 4, H302 Acute toxicity (dermal), Category 4, H312 Acute toxicity (inhal.), Category 4, H332 Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
trimethylolpropane triglycidylether	(CAS-No.) 30499-70-8	5 - 10	Skin corrosion/irritation, Category 1C, H314 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, category 1B, H317 Germ cell mutagenicity, Category 2, H341 Reproductive toxicity, Category 1B, H360 Hazardous to the aquatic environment — Chronic Hazard, Category 2, H411
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8	2.5 - 5	Acute toxicity (dermal), Category 5, H313 Serious eye damage/eye irritation, Category 1, H318 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402

Full text of H-statements: see section 16



# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.
Potential adverse human health effects and symptoms	No additional information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

##### 6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

##### 6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

### 6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Additional information	The product has a pasty consistency. Exposure limit values for respirable dusts are not relevant for this product.
------------------------	--

### 8.2. Appropriate engineering controls

Appropriate engineering controls	No specific measures identified.
Environmental exposure controls	No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Materials for protective clothing Long sleeved protective clothing

Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN 374

Eye protection Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection Wear suitable protective clothing



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey.
Odour	characteristic.
Odour threshold	No data available
pH	6.6
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	1.45 g/cm <sup>3</sup>
Solubility	insoluble in water.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	45 - 59 Pa·s 23 °C
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

<b>Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rabbit	1130 mg/kg (Rabbit)
<b>[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)</b>	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation Causes severe skin burns and eye damage.  
pH: 6.6

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Serious eye damage/irritation	Serious eye damage, category 1, implicit pH: 6.6
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Toxic to aquatic life.
Classification procedure (Hazardous to the aquatic environment, short-term (acute))	Calculation method
Hazardous to the aquatic environment, long-term (chronic)	Toxic to aquatic life with long lasting effects.
Classification procedure (Hazardous to the aquatic environment, long-term (chronic))	Calculation method

<b>butanedioldiglycidyl ether (2425-79-8)</b>	
LC50 fish 1	24 mg/l (96 h; Pisces) ECHA
LC50 other aquatic organisms 1	> 160 mg/l
NOEC (acute)	40 mg/l
Threshold limit algae 1	88930 mg/l (96 h; Algae)
<b>[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)</b>	
LC50 fish 1	55 mg/l (96 h; Cyprinus carpio; Young)
EC50 Daphnia 1	473 - 710 mg/l (48 h; Daphnia magna)
LC50 fish 2	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
Threshold limit algae 1	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit algae 2	250 mg/l (72 h; Selenastrum capricornutum)
<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
LC50 fish 1	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

### 12.2. Persistence and degradability

<b>HIT-RE 500 V3, A</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.
<b>Quartz (SiO2)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>butanedioldiglycidyl ether (2425-79-8)</b>	
Biochemical oxygen demand (BOD)	0.01982 g O <sub>2</sub> /g substance
<b>2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)</b>	
Persistence and degradability	Not readily biodegradable in water.

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### 12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.
Quartz (SiO <sub>2</sub> )	
Bioaccumulative potential	No bioaccumulation data available.
butanedioldiglycidyl ether (2425-79-8)	
Log Pow	-0.15
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Log Pow	-0.92 (Estimated value)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)
Log Pow	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

Quartz (SiO <sub>2</sub> )	
Ecology - soil	Low potential for mobility in soil.
butanedioldiglycidyl ether (2425-79-8)	
Log Pow	See section 12.1 on ecotoxicology
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Log Pow	See section 12.1 on ecotoxicology
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available
Other information	Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
14.1. UN number			
1759	1759	1759	1759
14.2. UN proper shipping name			
CORROSIVE SOLID, N.O.S. (trimethylolpropane	CORROSIVE SOLID, N.O.S. (trimethylolpropane	Corrosive solid, n.o.s. (trimethylolpropane	CORROSIVE SOLID, N.O.S. (trimethylolpropane

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

ADR	IMDG	IATA	RID
triglycidylether)	triglycidylether)	triglycidylether)	triglycidylether)
<b>Transport document description</b>			
UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1759 Corrosive solid, n.o.s. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>			
8	8	8	8
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)

E

#### - Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

#### - Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

### - Rail transport

Special provisions (RID)	274
Packing instructions (RID)	P002, IBC08, LP02, R001
Carriage prohibited (RID)	No

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

## SECTION 16: Other information

SDS Major/Minor	None
Issue date	13/05/2020
Revision date	13/05/2020
Supersedes	25/02/2019

Indication of changes:

Section	Changed item	Change	Comments
9	pH	Added	
14	Transport information	Modified	
16	Additional information	Added	

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE - Acute Toxicity Estimate  
 BCF - Bioconcentration factor  
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
 DMEL - Derived Minimal Effect level  
 DNEL - Derived-No Effect Level  
 IATA - International Air Transport Association  
 EC50 - Median effective concentration  
 IMDG - International Maritime Dangerous Goods  
 LC50 - Median lethal concentration  
 LD50 - Median lethal dose  
 LOAEL - Lowest Observed Adverse Effect Level  
 NOAEC - No-Observed Adverse Effect Concentration  
 NOAEL - No-Observed Adverse Effect Level  
 NOEC - No-Observed Effect Concentration  
 PBT - Persistent Bioaccumulative Toxic  
 PNEC - Predicted No-Effect Concentration  
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
 SDS - Safety Data Sheet  
 vPvB - Very Persistent and Very Bioaccumulative

Other information  
 None.



# HIT-RE 500 V3, A

## Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

---

Full text of H-statements:

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS\_UN\_Hilti

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*