



CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Issue date: 13/12/2021

Revision date:

:

Version: 1.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Mixture
Trade name	CF-F ECO / CF-I 50 ECO GV
UN-No. (ADR)	1950
Product code	BU Fire Protection Foam

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	PU installation foams
------------------------------	-----------------------

1.4. Supplier's details

Supplier

Hilti Saudi Arabia for Construction Tools LLC
King Fahd Street
P.O. Box 15930
SA 21454 Jeddah
Saudi Arabia
T +966 2 213 8400, F +966 2 697 4696
sa.customerservice@hilti.com

Department issuing data specification sheet

Hilti AG
Feldkircherstraße 100
FL 9494 Schaan
Liechtenstein
T +423 234 2111
product.compliance-fire.protection@hilti.com

1.5. Emergency phone number

Emergency number	Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49 (0)6132-84463 +966 2 213 8400
------------------	--

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Aerosol, Category 1	H222;H229	On basis of test data
Skin corrosion/irritation, Category 2	H315	Calculation method
Serious eye damage/eye irritation, Category 2	H319	Calculation method
Respiratory sensitisation, Category 1	H334	Calculation method
Skin sensitisation, Category 1	H317	Calculation method
Carcinogenicity, Category 2	H351	Calculation method
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	Calculation method
Specific target organ toxicity – Repeated exposure, Category 2	H373	Calculation method
Full text of H-statements: see section 16		

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)



Signal word (GHS UN)

Danger

Hazardous ingredients

4,4'-diphenylmethanediisocyanate, isomeres and homologues

Hazard statements (GHS UN)

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS UN)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe spray.

P280 - Wear eye protection, protective clothing, protective gloves.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
4,4'-diphenylmethanediisocyanate, isomeres and homologues	CAS-No.: 9016-87-9	25 – 60	Flammable liquids Not classified Acute toxicity (oral) Not classified Acute toxicity (dermal) Not classified Acute toxicity (inhal.), Category 4, H332 Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 2, H319 Respiratory sensitisation, Category 1, H334 Skin sensitisation, Category 1, H317 Carcinogenicity, Category 2, H351 Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation, H335 Specific target organ toxicity – Repeated exposure, Category 2, H373
isobutane (Propellant gas (Aerosol))	CAS-No.: 75-28-5	10 – 25	Flammable gases, Category 1A, H220 Gases under pressure : Compressed gas, H280 Acute toxicity (inhalation:gas) Not classified
Dimethyl ether (Propellant gas (Aerosol))	CAS-No.: 115-10-6	5 – 10	Flammable gases, Category 1A, H220 Gases under pressure : Compressed gas, H280 Hazardous to the aquatic environment – Acute Hazard Not classified
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6	5 – 10	Flammable gases, Category 1A, H220 Gases under pressure : Liquefied gas, H280
Reaction products of phosphoryl trichloride and 2-methyloxirane (TCPP)	CAS-No.: 13674-84-5	1 – 5	Acute toxicity (oral), Category 4, H302 Hazardous to the aquatic environment – Chronic Hazard, Category 3, H412

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Toxic fumes may be released. Vapours may form explosive mixture with air.

5.3. Special protective actions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site. After curing, the product can be disposed of with household waste.

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. May form flammable/explosive vapour-air mixture. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Heat and ignition sources

Keep away from heat and direct sunlight. Keep away from ignition sources.

Storage temperature

5 – 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

Environmental exposure controls

Avoid release to the environment.

Other information

Do not eat, drink or smoke during use.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Protective clothing. Safety glasses. Gloves. Avoid all unnecessary exposure.

Hand protection

Wear suitable gloves tested to EN374. Suitable for short-term work or as a splash guard: Nitrile rubber gloves (> 0.1 mm). In case of permanent product contact:

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0,35mm		
Disposable gloves	Butyl rubber	6 (> 480 minutes)	>0,35mm		

Eye protection

Chemical goggles or safety glasses

Skin and body protection

Wear suitable protective clothing

Respiratory protection

Not necessary with sufficient ventilation. Ensure good ventilation of the work station. Open windows during application to ensure natural ventilation. If the occupational exposure limit is exceeded: Wear appropriate mask. (e.g. gas filter type A1-P2 according to EN 14387)

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol
Colour	Manila.
Odour	characteristic.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability	Not available
Lower explosion limit	Not available
Upper explosion limit	Not available
Flash point	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not available
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50°C	Not available
Density	0.92 g/cm ³
Relative density	0.92
Relative vapour density at 20°C	Not available
Solubility	Not available
Particle size	Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

Explosive properties	Pressurised container: May burst if heated.
% of flammable ingredients	45.1 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
LD50 dermal	9400 mg/kg
LC50 Inhalation - Rat	0.49 mg/l

propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not classified

CF-F ECO / CF-I 50 ECO GV	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with Poecilia reticulata, 96 h, Poecilia reticulata, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with Daphnia magna, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
EC50 96h - Algae [1]	154.9 mg/l (ECOSAR v1.00, Algae, QSAR, Estimated value)
propane (74-98-6)	
EC50 96h - Algae [1]	12 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
isobutane (75-28-5)	
EC50 96h - Algae [1]	8.57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)
12.2. Persistence and degradability	
CF-F ECO / CF-I 50 ECO GV	
Persistence and degradability	No additional information available
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
Dimethyl ether (115-10-6)	
Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.
propane (74-98-6)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
isobutane (75-28-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
CF-F ECO / CF-I 50 ECO GV	
Bioaccumulative potential	No additional information available
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
BCF - Fish [1]	268.1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Kow)	10.46 (Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water (Log Kow)	0.1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
propane (74-98-6)	
Partition coefficient n-octanol/water (Log Kow)	1.1 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Kow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

CF-F ECO / CF-I 50 ECO GV	
Mobility in soil	No additional information available

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.

Dimethyl ether (115-10-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

propane (74-98-6)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

isobutane (75-28-5)	
Surface tension	No data available in the literature
Ecology - soil	Not applicable (gas).

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Tunnel restriction code (ADR)	D

Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
MFAG-No	126

Air transport

PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
CAO packing instructions (IATA)	203
Special provisions (IATA)	A145, A167, A802

Inland waterway transport

Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04

CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Number of blue cones/lights (ADN) 1

Rail transport

Special provisions (RID) 190, 327, 344, 625
 Limited quantities (RID) 1L
 Packing instructions (RID) P207, LP02

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date 12/13/2021

Full text of H-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. Not classified (Dermal)	Acute toxicity (dermal) Not classified
Acute Tox. Not classified (Inhalation:gas)	Acute toxicity (inhalation:gas) Not classified
Acute Tox. Not classified (Oral)	Acute toxicity (oral) Not classified
Aquatic Acute Not classified	Hazardous to the aquatic environment – Acute Hazard Not classified
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. Not classified	Flammable liquids Not classified
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer



CF-F ECO / CF-I 50 ECO GV

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Full text of H-statements:	
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

SDS_UN_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.